



MILITARY SOLUTIONS

Parflex fluoropolymer tubing products for military applications.



FLUOROPOLYMER TUBING




For Military Applications

From the last frontier into the depths of the sea, Parker Hannifin Fluoropolymer Tubing products keep the military moving. Whether its the smallest piece of tubing, a standard heat shrinkable tube or an extra flexible convoluted tube, the fluoropolymer product line delivers virgin tubing that performs in extreme high or low temperatures.

Parker is 100% committed to supporting our military. Fluoropolymer tubing is produced at the Parflex Division's Fort Worth facility under the Texloc brand. It is tested and certified to some of the most rigorous specifications in the industry.

Product Features:

- Compliant to Mil-Spec Certifications
- FDA Compliant
- Minimal longitudinal growth/shrinkage
- Unlimited shelf life
- Complete Traceability, Lot #, DOM
- Value added services include:
 - Cuffing
 - Custom sizes
 - Cut to length parts
 - Drilled tubing
 - Etched PTFE
 - Formed tubing for quick installation
 - Tube flanging
 - Tube flaring
 - Tube forming
 - Tube slitting
 - Wire reinforcement of convoluted tubing






Tubing Features:

- **PTFE Tubing:** Temperatures up to 500°F, Lowest coefficient of friction
- **FEP Tubing:** Temperatures up to 400°F, exceptional clarity, long continuous lengths
- **ETFE Tubing:** Temperatures up to 302°F, increased abrasion resistance

Applications

- Bundling
- Harnesses
- Electrical Insulation
- Robotics
- Split Loom
- Track Lighting Protection
- Beverage Lines



Typical Image	Specification*	Material	Product Description & Sizes
 Heatshrink	AS23053/11, Class 1	FEP	Sizes 3/8" to 1-1/2"; AWG 24 - AWG 0
	AS23053/11, Class 2	FEP	Sizes 3/32" to 2"
	AS23053/12, Class 1	PTFE	Sizes 1/8" to 1"
	AS23053/12, Class 2	PTFE	Sizes 1/8" to 1"; AWG 24 - AWG 0
	AS23053/12, Class 3	PTFE	Sizes 1/8" to 1"; AWG 24 - AWG 0
 Heatshrink	AS23053/12, Class 5	PTFE	Sizes 5/64" to 1-1/4"

[Visit the webpage](#)

*Products are dimensionally compliant to specifications;
May not be exact equivalents

 Convoluted	AS81914/1 Certified	PTFE	Convoluted, Standard Convolution, 81914/1 Sizes 3/16" to 2" I.D. Natural or Black
	AS81914/2	PTFE	Convoluted, Close Convolution, 81914/2 Sizes 3/16" to 2" I.D. Natural or Black
	AS81914/3	FEP	Convoluted, Standard Convolution, 81914/3 Sizes 3/16" to 2" I.D. Natural
	AS81914/4	FEP	Convoluted, Close Convolution, 81914/4 Sizes 3/16" to 2" I.D. Natural
	AS81914/5	ETFE	Convoluted, Close Convolution, 81914/5 Sizes 3/16" to 2" I.D. Natural
	AS81914/6	ETFE	Convoluted, Standard Convolution, 81914/6 Sizes 3/16" to 2" I.D. Natural


[Visit the webpage](#)

*Products are dimensionally compliant to specifications;
May not be exact equivalents

 Smoothbore	MIL-DTL-27267C	PTFE	PTFE Conductive Tubing Sizes 1/4" to 4" O.D. ; AWG 32 - AWG 0
	AMS 3655B	PTFE	PTFE Spaghetti Tubing, TFT AWG 32 - AWG 0
	AMS 3653G	PTFE	PTFE Spaghetti Tubing, TFS AWG 30 - AWG 0

[Visit the webpage](#)

*Products are dimensionally compliant to specifications;
May not be exact equivalents

 Corrugated	FEP	ASTM D3296-03
		
	Sizes 1/4" to 2-1/2" I.D.	

[Visit the webpage](#)

For technical information on these products, download Catalog 4660 at www.parker.com/pfd



Parker Hannifin Corporation
Parflex Division
1300 North Freedom Street
Ravenna, Ohio 44266
phone 330 296 2871
fax 330 296 8433
www.parker.com/pfd

Bul. 4660-4150-Military 05/26

© 2026 Parker Hannifin Corporation

